Hammer Camera Cranes

440 E. Easy St. #3 Simi Valley, Ca 93065 805-526-2626

WH410 Features & Specs:

- Two-channel
- 2.4GHz frequency range
- 7 kHz wide band audio
- Up to 15 belt packs and/or all-in-one headsets on a single system

Up to 12 hours of battery life

Audio Antenna

Channels: 2 audio channels Internal

Frequency Range: 2400 MHz – 2483.5 MHz

Frequency Response: 200 Hz – 7 kHz

Antenna: Internal, horizontal/vertical diversity **Transmitter**

Headset Connector: 4-pin, mini-DIN Type: Frequency Hopping, Transmit Power:

Spread Spectrum (FHSS)

100mW burst

Microphone: Electret Modes: Momentary or Latch Type: Gaussian filtered

Headset Output: 160mW into 32 Ohms

FSK, TDMA

System Distortion: <2%

ppm

Controls: Power, Volume-Up, Volume-Down, A, B, ISO Harmonics/Spurious:

Exceeds FCC

Indicators: Dual-color LED (red/green) and ETSI specifications

Battery Requirements: 3.6V lithium-ion

Battery Life: Up to 12 hours

Receiver **Environmental**

Type: Frequency Hopping, Spread Spectrum (FHSS) 32°F to +122°F

RF Sensitivity: <-90dBm w 10-3 BER $(0^{\circ}C \text{ to } +50^{\circ}C)$

Frequency Stability: 13 ppm

Distortion: <2% Weight

3.5 oz (0.10kg) including battery

Frequency Stability: 13