

Active Head- Gyro-stabilized head

The design of this head allows you to use all of the common types of film and digital cameras. The head is also suitable for small and mid-size 3d rigs. It allows you to achieve high stabilization performance even with the longest and the heaviest lens, such as Optimo 24-290.

The head is equipped with a digital lens control system that adds functionality and flexibility. It's available with a variety of control options such as Hand wheels, Joystick and Pan Bar*.

- Improved stabilization level which allows you to achieve a balanced picture even under extremely rough and difficult operating conditions
- High angular velocity on all axes Compact Size and light weight
- Fast and effective rebalancing and calibration
- 360 degree pan and roll function
- Axis position indication
- Solid and reliable construction Quick Assembly
- Remote controlled handling of lens Parameters (Focus, Iris, Zoom) Auto horizon
- Control capability by cable or wireless

Height	881 mm/ 34.69 in
Width	703 mm/ 27.67 in
Depth	667 mm/ 26.26 in
Power Supply AC	(90-264V); 1kW(peak)
Power Supply DC	(19-72V); 1kW(peak)
Pan angular speed	270 deg/sec
Tilt angular speed	270 deg/sec
Roll angular speed	270 deg/sec
Weight	32 kg/ 70.5 lbs
Maximum usable focal length	290 mm
Payload	45 kg/ 99.2 lbs

This model fits for all of the common types of Cranes,
Remote Controlled Platforms and Helicopter/Aerial Systems

Active Head- Gyro-stabilized head

