## Magic head & Control Desk Specs:

## **Magic Head**

- Maximum Load: 44 lbs / 20 Kg

- Own weight: 40 lbs / 18 Kg

- Dimensions: 7" x 22" x 27.5" / 180 mm x 560 mm x 700 mm

- Clearance for TILT axis of the camera: max. 21.25" / 540 mm

- Maximum speed: 1/4rev/s (90°), (360°/4sec.) for all axes.

- Adjusting/balance o the camera for both axes.

- Cable connecting head with desktop: 164' / 50 m.

- FOCUS/ZOOM cables for CANON and FUJINON lenses.

- Control Desktop/Panel.

- Stabilized power supply.

- Mitchell adapter

- Transport case: 29.5" x 31.5" x 23.6" / 750x800x600

- Total weight of the transport set: 159 lbs / 72kg

## The control desktop/panel contains:

The standard length of the cable used to connect the desktop with the head is 164 feet (50m). This can be extended up to 492 feet (150m).

- JOYSTICK Control.

Separate adjustment of SPEED and FLUID soft start/end for both axes, switches for changes in directions DIR and also LOCK buttons for PAN and TILT axes.

- HOME button returns head to 'power up' position.
- FOCUS rotate regulator and ZOOM tilt for TV cameras.
- Adjustment of LIMIT HI and LIMIT LOW range for FOCUS function, switch of working direction DIR and FLUID regulator.
- ZOOM speed adjustment, button of maximum SPEED MAX and switch of working direction DIR.